



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	---------------------------	--	----------------------	--	-------------------

TECHNICAL DATA	STD
EXTERNAL DIMENSIONS	
width	590 mm
depth	600 mm
height	850 mm
WEIGHT	56.5 kg
VOLTAGE	230V 50Hz
POWER REQUIRED	3450 W
WATER HARDNESS	2-8 °F
INLET WATER PRESSURE	200-400 kPa
CROCKERY DIMENSIONS	
plates diameter	345 mm
dishes max. height	320 mm
RACK DIMENSIONS	500X500 mm
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060
WASHING CYCLES (s)	1 (120)
WATER SUPPLY 55°C	
racks/h(*) ⁽¹⁾	30
WATER SUPPLY 10°C	
racks/h(*) ⁽¹⁾	14
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L
BOILER CAPACITY	5.7 L
BOILER HEATING ELEMENT	2800 W
RINSING TEMPERATURE (SET)	85°C
TANK CAPACITY	29 L
TANK HEATING ELEMENT	2700 W
TANK TEMPERATURE (SET)	55°C
PUMP POWER	650 W (340 L/min ^{***})
DRAIN PUMP (optional)	25 W h MAX draining 0.8m(40 L/min ^{***})
NOISE	63 dB(A)

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.